



CONNECTED LIGHTING CONTROLS

With the Zen HQ platform, easily integrate lighting controls for off-site management of your lighting systems. Customizable schedules allow for lights to automatically turn on, off, or dim throughout your facilities according to your business needs.

ON, OFF OR DIM

Control the on/off state with the Zen HQ load controller, or choose brightness levels with ZigBee connected switches. Make changes manually at the device level, or use the Zen HQ interface for simple remote control.

GROUPING

Group multiple lighting devices together within or across facilities to easily change settings and schedules with the click of a button.

SCHEDULING

Easily schedule lighting to turn on, off or dim at a National, Regional, or Site level. When creating a schedule, select which days the schedule is valid for, and select start and end times in 5-minute intervals. Temporarily override schedules during holiday hours.

EASY INSTALLATION

Set up is so simple, it can be installed within a day by a certified electrician.



LOAD CONTROLLER

SPECIFICATIONS

INPUT VOLTAGE

120 VAC

INPUT FREQUENCY

60 HZ

NOMINAL OPERATING TEMPERATURE

77°F, 25°C

NUMBER OF CIRCUITS CONTROLLED

• 6 PER DEVICE
• 10 PER DEVICE

SYSTEM CONTROLS

MODES ON/OFF

CONNECTIVITY

WIRELESS PROTOCOL

WIRELESS RANGE

UP TO 100 FT FROM
CONTROLLER OR
CLOSEST ZIGBEE DEVICE

SETUP & INSTALLATION

INSTALLATION REQUIRED
INSTALLATION BY A
CERTIFIED ELECTRICIAN

DIMENSIONS

LOAD CONTROLLER 11.93" x 10.15" x 4.08"

MAXIMUM CIRCUIT RATING PER POLE

RESISTIVE RATING 25 AMPS
MOTOR RATING 10 AMPS
LAMP RATING 20 AMPS

DIMMING SWITCHES

SPECIFICATIONS

INPUT VOLTAGE 120 VAC
INPUT FREQUENCY 60 HZ
NOMINAL OPERATING TEMPERATURE 77°F, 25°C

LOAD RATINGS

INCANDESCENT MAXIMUM LOAD: 600W

· LED/CFL: 150W

SYSTEM CONTROLS

MODES ON/OFF/DIM

CONNECTIVITY

WIRELESS PROTOCOL

WIRELESS RANGE

UP TO 100 FT FROM
CONTROLLER OR
CLOSEST ZIGBEE DEVICE

SETUP & INSTALLATION

INSTALLATION RECOMMEND
INSTALLATION BY A
CERTIFIED ELECTRICIAN

DIMENSIONS

IN-WALL SMART SWITCH 4.17" x 2.13" x 1.82"